






VERSATILE is a widely tested product under numerous conditions. This tile comes in specifications that are unmatched for its cost.

SPECIFICATIONS

Overall Cover Width: 1,077 mm ± 5 mm Effective Width Cover: 1,015 mm ± 5 mm Length/Square Meter: 1,082 mm



600mm upwards in multiples of 300mm Lengths:

Maximum recommended length for 0.32mm is 6m

Base Material: ZINCAL © Coils made using world class patented

metal coating technology

Paint Systems: Colour Plus, Optima & Optima Plus

Finish: Matt finish

Thicknes: 0.32mm, 0.4mm, (±10%)

Minimum 0.32mm (28g) Maximum 0.40mm (22g)

BENEFITS



Cost Efficiency



Light Weight



Long Lasting



Secure



Heritage



Repair Free



Performance

Extra Wide

Engineered Roofing

Fashionable & Stylish

Speed of Installation

& Minimised Wastage

Going Green



rainwater – Once installed collection of rainwater runoff has many benefits for domestic and agricultural use.



Disposal & Recycling –Disposal if needed will be by the standard steel recycling process of recycling in a

Manufacturing process - majority of the water used in the manufacture of this material is recycled. Air and fume emissions comply with

Fixing Procedure

Recommended structure

Custom designed light gauge steel structure or Minimum 50 x 50 mm purlins (recommended)

100 x 50mm (trusses/rafters) for timber structures.

Wherever possible, it is recommended that one use single lengths to cover each run of roof from ridge/Apex to eave (avoid end-lapping) for better aesthetics, economy and reduced chance of leakage.

Maximum Purlin Spacing: 600 mm centres.

Roofing Procedure: Always overlap the left edge of the sheet

over the right edge (looking form outside)

Roof Pitch: The tiles can be used on roof pitches from

minimum 12.5°

Crest Fixing

FIXTILE, self drilling screws, for light gauge steel structures (recommended), are fixed through the crest of the profile ribs using an electric screw-gun (drill). Screws must be used in conjunction with appropriate EPDM washers.

Alternative option is to install using traditional galvanized twisted shank roofing nails hammered into place using appropriate UPVC caps and washers, (Not recommended owing to inferior coating of the nails).

FEATURES

Sheets

- Continuous length profile increases visual uniformity
- Reduces chance of leakage
- Lightweight safer to lift and install while enabling the supporting structure to be less bulky / costly
- No underlays needed
- Rapid roof coverage
 - Large panel size enables roofing to be completed faster
 - Easy & secure roofing sheets are fixed to the roof structure
- World class patented coating technology
- UBL mark of quality each sheet is inspected over 6 times before dispatch
- Engineered to prevent leakage by capillary action.
- A wide color range available in 7 standard colors

COLOUR CHART







